

What is claimed is:

1. A cleaning device for cleaning an orifice surface of an inkjet head and a different level member having a surface at a different level than the orifice surface, the different level member forming a step between the orifice surface and the surface of the different level member, the orifice surface being formed with a row of nozzle orifices, the cleaning device comprising:

an air flow generating unit formed with a suction hole positioned at the nozzle orifice, the air flow generating unit generating a spiraling current by sucking air into the suction hole, the air flow generating unit sucking ink from the nozzle orifice by drawing the ink in with the spiraling current.

2. The cleaning device as claimed in claim 1, wherein the air flow generating unit sucks air in through the suction hole at asymmetrical flow velocity and flow rate about the row of nozzle orifices.

3. The cleaning device as claimed in claim 1, wherein the air flow generating unit includes:

a suction hole member formed with the suction hole;

a negative pressure generator that generates a negative pressure at the suction hole; and

a positioning unit that positions the suction hole member at a suction position wherein the suction hole

confronts the nozzle orifice and the different level member.

4. The cleaning device as claimed in claim 3, wherein a gap is formed between the suction hole member and at least one of the orifice surface and the different level member, the gap having a size that is asymmetric about the row of nozzle orifices.

5. The cleaning device as claimed in claim 4, further comprising a stage unit that moves the suction hole member following the row of nozzle orifices formed in the orifice surface.

6. The cleaning device as claimed in claim 3, wherein the suction hole member is formed with a plurality of suction holes, the negative pressure generator generates the negative pressure at at least two adjacent ones of the plurality of suction holes at a time while sequentially suctioning the plurality of suction holes.

7. The cleaning device as claimed in claim 3, wherein the suction hole member disposed at the suction position deforms while pressing against the orifice surface and the different level member without contacting the nozzle orifice.

8. The cleaning device as claimed in claim 3, wherein the suction hole member disposed at the suction position is distanced from the orifice surface without contacting the orifice surface.

9. A cleaning device for cleaning an orifice surface

of an inkjet head and a different level member attached to the orifice surface, the different level member having a surface at a different level than the orifice surface, thereby forming a step between the orifice surface and the surface of the different level member, the orifice surface being formed with a row of nozzle orifices, the cleaning device comprising:

an air flow generating unit formed with a suction hole positioned at the nozzle orifice, the air flow generating unit generating a spiraling current by sucking air into the suction hole, the air flow generating unit sucking ink from the nozzle orifice by drawing the ink in with the spiraling current.

10. An inkjet recording device comprising:

an inkjet head including:

an orifice surface formed with a row of nozzle orifices;

a different level member having a surface at a different level than the orifice surface, the different level member forming a step between the orifice surface and the surface of the different level member; and

an ink ejection unit that ejects ink droplets from each of the nozzle orifices; and

the cleaning device of claim 1.

11. The inkjet recording device as claimed in claim

10, further comprising a movement mechanism that moves the inkjet head between a recording position and a cleaning position, the different level member including a charge deflection electrode formed with an ink reception portion.

5           12. The inkjet recording device as claimed in claim 10, wherein the air flow generating unit sucks air in through the suction hole at asymmetrical flow velocity and flow rate about the row of nozzle orifices.

10           13. The inkjet recording device as claimed in claim 10, wherein the air flow generating unit includes:

          a suction hole member formed with the suction hole;

          a negative pressure generator that generates a negative pressure at the suction hole; and

15           a positioning unit that positions the suction hole member at a suction position wherein the suction hole confronts the nozzle orifice and the different level member.

20           14. The inkjet recording device as claimed in claim 13, wherein a gap is formed between the suction hole member and at least one of the orifice surface and the different level member, the gap having a size that is asymmetric about the row of nozzle orifices.

25           15. The inkjet recording device as claimed in claim 14, further comprising a stage unit that moves the suction hole member following the row of nozzle orifices formed in the orifice surface.

16. The inkjet recording device as claimed in claim 13, wherein the suction hole member is formed with a plurality of suction holes, the negative pressure generator generates the negative pressure at at least two adjacent  
5 ones of the plurality of suction holes at a time while sequentially suctioning the plurality of suction holes.

17. The inkjet recording device as claimed in claim 13, wherein the suction hole member disposed at the suction position deforms while pressing against the orifice surface  
10 and the different level member without contacting the nozzle orifice.

18. The inkjet recording device as claimed in claim 13, wherein the suction hole member disposed at the suction position is distanced from the orifice surface without  
15 contacting the orifice surface.

19. The inkjet recording device as claimed in claim 10, wherein the different level member is attached to the orifice surface.